



Product Name: BLACK SATIN ARTERIAL EMBALMING FLUID

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

BLACK SATIN ARTERIAL EMBALMING FLUID

Synonyms

BLACK SATIN

Product Use

Funeral Home Embalming Products

Restrictions on Use

This product should only be used by Licensed Embalmers

Details of the supplier of the safety data sheet

Dr. G.H. Michel - Restor-Skin Company

PO Box 337

202 Sixth Street

East Brady, PA 16028

Phone: 1-800-635-3403

Emergency Phone #: 1-724-526-3565

E-mail: fourcogs16028@yahoo.com

Product Code

Product Size(s): 16 oz. Bottles

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 4

Acute Toxicity - Oral - Category 3

Acute Toxicity - Dermal - Category 3

Acute Toxicity - Inhalation - Vapor - Category 2

Skin Corrosion/Irritation - Category 1

Serious Eye Damage/Eye Irritation - Category 1

Respiratory Sensitization - Category 1A

Skin Sensitization - Category 1A

Germ Cell Mutagenicity - Category 1A

Carcinogenicity - Category 1A

Reproductive Toxicity - Category 1A

Specific Target Organ Toxicity - Single Exposure - Category 1 (nervous system , respiratory system , Central Nervous System , heart , kidneys , body , optic nerve , retina , systemic toxicity , eyes)

Specific Target Organ Toxicity - Single Exposure - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (Central Nervous System , respiratory system , heart , kidneys , eyes , retina)

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Hazardous to the Aquatic Environment - Acute - Category 2

Hazardous to the Aquatic Environment - Chronic - Category 3

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Combustible liquid.

Toxic if swallowed.

Toxic in contact with skin.

Fatal if inhaled.

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs.

May cause damage to organs.

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear respiratory protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Response

In case of fire: Use appropriate media to extinguish.

Immediately call a POISON CENTER or doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Specific treatment is urgent (see label).

Collect spillage.

Storage

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Statement of Unknown Toxicity

76.384% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
50-00-0	Formaldehyde	15-20
107-21-1	Ethylene glycol	10-15
25322-58-3	Carbowax 400	10-15
67-56-1	Methyl alcohol	5-10
57-55-6	1,2-Propanediol	1-5
8039-09-6	PEG-75 Lanolin	>1
No CAS	Dye	<1

The chemical identity and/or percentage of composition is being withheld as a trade secret.

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice/attention.

Eyes

IF IN EYES: Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

Most Important Symptoms/Effects

Acute

Toxic if swallowed. Toxic in contact with skin. Fatal if inhaled. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Causes damage to central nervous system, nervous system, respiratory system, heart, kidneys, optic nerve, body, retina, systemic toxicity, eyes. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed

May produce an allergic reaction. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: central nervous system, heart, respiratory system, kidneys, retina, and eyes. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical, water spray, alcohol-resistant foam

Unsuitable Extinguishing Media

Do not use water jet.

Special Hazards Arising from the Chemical

Combustible liquid.

Hazardous Combustion Products

Oxides of carbon, formaldehyde gas

Fire Fighting Measures

Move container from fire area if it can be done without risk. Dike far ahead of liquid spill for collection and later disposal. Do not scatter spilled material with extinguishing agent. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Do not get water inside container. Cool containers with water spray until well after the fire is out. Vapors may travel to ignition source and flashback. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in fire. Avoid inhalation of material or combustion by-products. Containers may rupture or explode if exposed to heat.

Special Protective Equipment and Precautions for Firefighters

Wear personal protective clothing and equipment such as self-contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Wear fire/flame resistant/retardant clothing. All equipment used when handling the product must be grounded. Eliminate all sources of ignition. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if safe to do so. Prevent entry into waterways, sewers, basements, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb with earth, sand or other non-combustible material and transfer to container. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces.

Environmental Precautions

Collect spillage. Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Do not breathe vapor or mist. Wash thoroughly after handling. Wear respiratory protection. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Do not allow product to evaporate to dryness.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Further information on storage conditions: Keep away from heat, sparks, open flame or other ignition sources.

Keep away from incompatible materials.

Incompatible Materials

Strong acid

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

Formaldehyde	50-00-0
ACGIH:	0.3 ppm Ceiling
NIOSH:	0.016 ppm TWA
	0.1 ppm Ceiling 15 min
	20 ppm IDLH
OSHA (US):	0.75 ppm TWA
	2 ppm STEL (See 29 CFR 1910.1048) 15 min ; 0.5 ppm Action Level (See 29 CFR 1910.1048) ; 0.75 ppm TWA (See 29 CFR 1910.1048)
	2 ppm STEL (see 29 CFR 1910.1048)
Mexico:	2 ppm Ceiling ; 3 mg/m3 Ceiling
Ethylene glycol	107-21-1
ACGIH:	100 mg/m3 Ceiling aerosol only
Europe:	20 ppm TWA ; 52 mg/m3 TWA
	Possibility of significant uptake through the skin
	40 ppm STEL ; 104 mg/m3 STEL
Mexico:	100 mg/m3 Ceiling aerosol
Methyl alcohol	67-56-1
ACGIH:	200 ppm TWA
	250 ppm STEL
	Skin - potential significant contribution to overall exposure by the cutaneous route
NIOSH:	200 ppm TWA ; 260 mg/m3 TWA
	250 ppm STEL ; 325 mg/m3 STEL
	Potential for dermal absorption
	6000 ppm IDLH
Europe:	200 ppm TWA ; 260 mg/m3 TWA
	Possibility of significant uptake through the skin
OSHA (US):	200 ppm TWA ; 260 mg/m3 TWA
Mexico:	200 ppm TWA VLE-PPT ; 260 mg/m3 TWA VLE-PPT
	250 ppm STEL [PPT-CT] ; 310 mg/m3 STEL [PPT-CT]
	Skin - potential for cutaneous absorption

EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures

There are no biological limit values for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)**Methyl alcohol (67-56-1)**

15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment**Eye/face protection**

Wear chemical safety goggles with a face shield or chemical splash hood. Eye wash fountain and emergency showers are recommended.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

Respiratory protection is required for not sufficiently ventilated working places and during the spraying processing.

Glove Recommendations

Wear appropriate chemical resistant gloves: neoprene, rubber gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	clear, red, liquid	Physical State	liquid
Odor	Formaldehyde	Color	clear, red
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	212 °F (approx.)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	68.5 °C (155 °F)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	Not available	Molecular Weight	Not available

Other Information

No additional information is available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Hazardous polymerization is not expected to occur.

Conditions to Avoid

Keep away from heat, sparks, open flame and other ignition sources. Keep away from incompatible materials.

Incompatible Materials

Strong acid,

Hazardous decomposition products

Oxides of carbon, formaldehyde gas

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure**Inhalation**

Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

Toxic in contact with skin. Causes severe burns. May cause allergic skin reaction.

Eye Contact

Causes serious eye damage.

Ingestion

Toxic if swallowed.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Formaldehyde (50-00-0)

Oral LD50 Rat 100 mg/kg

Dermal LD50 Rabbit 270 mg/kg

Inhalation LC50 Rat 0.578 mg/L 4 h

Ethylene glycol (107-21-1)

Oral LD50 Rat 4700 mg/kg

Dermal LD50 Rat 10600 mg/kg

Methyl alcohol (67-56-1)

Oral LD50 Rat 6200 mg/kg

Inhalation LC50 Rat 22500 ppm 8 h

1,2-Propanediol (57-55-6)

Oral LD50 Rat 20 g/kg

Dermal LD50 Rabbit 20800 mg/kg

Product Toxicity Data

Acute Toxicity Estimate

Dermal	448.3384 mg/kg
Inhalation - Vapor	0.7454 mg/L
Oral	207.7375 mg/kg

Immediate Effects

Toxic if swallowed. Toxic in contact with skin. Fatal if inhaled. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Causes damage to central nervous system, respiratory system, heart, kidneys, nervous system, body, optic nerve, retina, systemic toxicity, eyes. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects

May produce an allergic reaction. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: kidneys, respiratory system, central nervous system, heart, eyes, retina. May cause damage to organs through prolonged or repeated exposure.

Irritation/Corrosivity Data

Causes severe skin burns and eye damage. May cause respiratory irritation.

Respiratory Sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

Formaldehyde	50-00-0
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100F [2012] ; Monograph 88 [2006] ; Monograph 62 [1995] ; Supplement 7 [1987] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen
DFG:	Category 4 (no significant contribution to human cancer)
OSHA:	Present
OSHA:	see 29 CFR 1910.1048
NIOSH:	potential occupational carcinogen
Ethylene glycol	107-21-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

May cause genetic defects.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

nervous system, Central Nervous System, respiratory system, heart, kidneys, body, optic nerve, retina, systemic toxicity, eyes

Specific Target Organ Toxicity - Repeated Exposure

Central Nervous System, respiratory system, heart, kidneys, eyes, retina

Aspiration hazard

No data available for this product.

Medical Conditions Aggravated by Exposure

No data available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Formaldehyde	50-00-0
Fish:	LC50 96 h Pimephales promelas 22.6 - 25.7 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 1510 µg/L [static]; LC50 96 h Brachydanio rerio 41 mg/L [static]; LC50 96 h Oncorhynchus mykiss 0.032 - 0.226 mL/L [flow-through]; LC50 96 h Oncorhynchus mykiss 100 - 136 mg/L [static]; LC50 96 h Pimephales promelas 23.2 - 29.7 mg/L [static]
Invertebrate:	LC50 48 h Daphnia magna 2 mg/L IUCLID ; EC50 48 h Daphnia magna 11.3 - 18 mg/L [Static] EPA
Ethylene glycol	107-21-1
Fish:	LC50 96 h Oncorhynchus mykiss 41000 mg/L; LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L [static]; LC50 96 h Lepomis macrochirus 27540 mg/L [static]; LC50 96 h Oncorhynchus mykiss 40761 mg/L [static]; LC50 96 h Pimephales promelas 40000 - 60000 mg/L [static]; LC50 96 h Poecilia reticulata 16000 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 46300 mg/L IUCLID
Methyl alcohol	67-56-1
Fish:	LC50 96 h Pimephales promelas 28200 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]; LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static]; LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through]
1,2-Propanediol	57-55-6
Fish:	LC50 96 h Oncorhynchus mykiss 51600 mg/L [static]; LC50 96 h Oncorhynchus mykiss 41 - 47 mL/L [static]; LC50 96 h Pimephales promelas 51400 mg/L [static]; LC50 96 h Pimephales promelas 710 mg/L
Algae:	EC50 96 h Pseudokirchneriella subcapitata 19000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L [Static] EPA

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. The responsibility for proper waste disposal lies with the owner of the waste. Hazardous Waste Number(s): D001, D002. Toxic.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: CORROSIVE LIQUIDS, TOXIC, N.O.S., (Contains: Formaldehyde)

Hazard Class: 8

UN/NA #: UN2922

Packing Group: III

Required Label(s): 8, 6.1

IATA Information:

Shipping Name: CORROSIVE LIQUID, TOXIC, N.O.S., (Contains: Formaldehyde)

Hazard Class: 8

UN#: UN2922

Packing Group: III

Required Label(s): 8, 6.1

ICAO Information:

Shipping Name: CORROSIVE LIQUID, TOXIC, N.O.S., (Contains: Formaldehyde)

Hazard Class: 8

UN#: UN2922

Packing Group: III

Required Label(s): 8, 6.1

IMDG Information:

Shipping Name: CORROSIVE LIQUID, TOXIC, N.O.S., (Contains: Formaldehyde)

Hazard Class: 8

UN#: UN2922

Packing Group: III

Required Label(s): 8, 6.1

TDG Information:

Shipping Name: CORROSIVE LIQUID, TOXIC, N.O.S., (Contains: Formaldehyde)

Hazard Class: 8

UN#: UN2922

Packing Group: III

Required Label(s): 8, 6.1

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Formaldehyde	50-00-0
SARA 302:	500 lb TPQ
SARA 313:	0.1 % de minimis concentration
CERCLA:	100 lb final RQ ; 45.4 kg final RQ
OSHA (safety):	1000 lb TQ
SARA 304:	100 lb EPCRA RQ
Ethylene glycol	107-21-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
Methyl alcohol	67-56-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances list:

Component	CAS	CA	MA	MN	NJ	PA
Formaldehyde	50-00-0	Yes	Yes	Yes	Yes	Yes
Ethylene glycol	107-21-1	Yes	Yes	Yes	Yes	Yes
Methyl alcohol	67-56-1	Yes	Yes	Yes	Yes	Yes
1,2-Propanediol	57-55-6	No	No	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Formaldehyde	50-00-0
Carc:	carcinogen , 1/1/1988 (gas)
Ethylene glycol	107-21-1
Repro/Dev. Tox	developmental toxicity , 6/19/2015 (ingested)
Methyl alcohol	67-56-1
Repro/Dev. Tox	developmental toxicity , 3/16/2012

Canada Regulations

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Formaldehyde	50-00-0	0.1 %
Ethylene glycol	107-21-1	1 %
Methyl alcohol	67-56-1	1 %
1,2-Propanediol	57-55-6	1 %

Component Analysis - Inventory

Formaldehyde (50-00-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes

Ethylene glycol (107-21-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

Methyl alcohol (67-56-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

1,2-Propanediol (57-55-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes

PEG-75 Lanolin (8039-09-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
No	No	No	No	No	No	No	No	No	No	No	No	Yes

Section 16 - OTHER INFORMATION**NFPA Ratings**

Health: 3 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

New SDS: April 28, 2016 / SDS Update Rev 1: October 10, 2016 / SDS Update Rev 2: May 17, 2018

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory; KECL - Korea Existing Chemicals List; KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorization, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information**Disclaimer:**

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.